

PRODUCT DATA SHEET

AFB 820

Tyre Construction: Bias

Type: Tube Less

Main Applications: Agro-Forestry

TRA Code: R-1



Salient Features:

Robust Lug Design:

Combination of robust lugs used in forestry applications & good self-cleaning properties.

Flat and Wider Tread:

Excellent stability during vehicle operation.

Specially Designed Tread Compound:

Ensures longer tyre life in forestry application.



Technical Data



Size	Recomm. Rim	Alternate Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)			
			SW	OD					Speed (kmph) (mph)			
			mm	mm					Mixed Application			
			inch	inch					10	20	30	40
								bar	6	12	19	25
								psi	6	12	19	25
18.4-26	16	W15L, DW16A	467	1450	656	4337	16 PR	2.5	6000	4920	4280	4000
			18.4	57.1	25.8	170.7	156 A8	36	13220	10840	9430	8810

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ **E:** enquiry@ascensotyres.com ■ **W:** www.ascensotyres.com