

PRODUCT DATA SHEET

BOSS TD 15

Tyre Construction: Bias

Type: Tube Type

Main Applications: Tractor

TRA Code: R-1



Salient Features:

Unique Mud Breaker:

- Excellent self-cleaning properties during field operation.

Dual-angle Lug Design:

- Provides unbeatable traction.

High Non-skid Depth:

- Best-in-class mileage.



Technical Data



Size	Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR, LI&SI	Inflation Pressure	Recommend load, kg (lbs)
		SW	OD					Speed, km/h (mph)
		mm	mm	mm	mm		bar	30
		inch	inch	inch	inch		psi	19
12.4-28	W11	315	1260	582	3768	12PR	2.5	1650
		12.4	49.6	22.9	148.3	125A6	36	3630
13.6-28	W12	345	1310	603	3918	12PR	2.3	1800
		13.6	51.6	23.7	154.3	128A6	33	3960
14.9-28	W13	378	1365	625	4082	12PR	2.3	2120
		14.9	53.7	24.6	160.7	134A6	33	4670
16.9-28	W15L	429	1435	654	4292	12PR	2.4	2725
		16.9	56.5	25.7	169.0	143A6	35	6000
18.4-30	W16L	467	1552	707	4642	14PR	2.7	3550
		18.4	61.1	27.8	182.8	152A6	39	7820

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

