

# PRODUCT DATA SHEET

## ***BOSS TS 10***

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** Tractor

**TRA Code:** F-2



### ***Salient Features:***

**Specially designed CCR Compound:**

- Puncture and cut resistance.
- Extra mileage.

**Wider Centre Rib:**

- Optimum road contact for better steering control.



# Technical Data



Size	Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR, LI&SI	Inflation Pressure	Recommend load, kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm	mm				mm	mm	bar	30
		inch	inch				inch	inch	psi	19
6.00-16	4.50E	165	732	338	2189	8 PR	4.5	670		
		6.5	28.8	13.3	86.2	94 A6	65	1470		
6.50-16	4.50E	175	761	349	2276	8PR	4.2	750		
		6.9	30.0	13.8	89.6	98 A6	61	1650		
7.50-16	5.50F	205	805	368	2408	8PR	3.7	875		
		8.1	31.7	14.5	94.8	103 A6	54	1930		

Note: All tyres confirm to ETRTO standards

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

