

## **PRODUCT DATA SHEET**

FFB 840

**Tyre Construction:** Bias

**Type:** Tube Tyre

Main Applications: Forestry Forwarder

TRA Code: LS-2



## Salient Features:

- FFB 840 is a bias steel-belted tire, suitable for forestry applications with forwarders and harvesters.
- The unique tread design and lug angle provide high traction and low slip abilities for improved fuel economy.
- With extensive inter-lug space provides Excellent self-cleaning properties and functions well with or without tracks, but tracks can be added for more demanding environments.
- The tire is equipped with reinforced steel belt for increased resistance to punctures and high load carrying capacity.
- The Reinforced bead area provides resistance to rim slip.
- Large tread width contributes to low soil compaction and driver comfort by providing a wider footprint.
- A Special tread and sidewall compound coupled with robust sidewalls and a high under tread, offers enhanced puncture resistance.







Size	Recomm. Rim	Unloaded Dimension		Loaded	Dolling		Inflation	Recommended load (kg) (lbs)					
								Speed (kmph) (mph)					
		sw	OD	Static Radius	Rolling Circumference	LI/SI or PR	Pressure	Forestry Service (LT)	Skidder Service (HT)	Road Application			
		mm	mm	mm	mm		bar	10	10	20	30	40	
		inch	inch	inch	inch		psi	6	6	16	19	25	
710/40-22.5 (SB)	AG24.00	705	1170	533	3513	20PR 161A8 HT -161A2 LT -168A2	5	5600	4625	5690	4950	4625	
		27.8	46.1	21.0	138.3		73	12330	10190	12530	10900	10190	
600/55-26.5 (SB)	AG20.00	600	1345	614	4039	20PR 165A8 HT -165A2 LT -172A2	5	6300	5150	6330	5510	5150	
		23.6	53	24.2	159		73	13880	11340	13940	12140	11340	
710/45-26.5 (SB)	AG24.00	705	1345	614	4039	20PR 168A8 HT -168A2 LT -175A2	5	6900	5600	6890	5990	5600	
		27.8	53	24.2	159		73	15200	12330	15180	13190	12330	
800/40-26.5 (SB)	AG28.00	800	1345	614	4039	20PR 170A8 HT -170A2 LT -177A2	5	7300	6000	7380	6420	6000	
		31.5	53	24.2	159		73	16080	13220	16260	14140	13220	

Note: SB-Steel Belted

Note: All tyres confirm to ETRTO standards