

PRODUCT DATA SHEET

FLB 681

Tyre Construction: Bias

Type: Tube Type

Main Applications: Forklift

TRA Code: NHS



Salient Features:

Specially Designed Tread:

Ensures optimum load distribution with wide footprint for better stability.

Unique Block Pattern:

- Ensures resistance against abrasions, punctures, and impacts.
- Strong casing for high load applications.



Technical Data



Size	Recom. Rim	Unloaded Dimensions		Static Load Radius	Rolling Circumference	PR	Inflation Pressure	Recommended load (kg) (lbs)	
		SW	OD					Speed (kmph) (mph)	
		mm	mm					Load Wheel	Steer Wheel
		inch	inch					25 kmph	25 kmph
7.50-16	6.0	223	835	380	2497	16	10.3	3068	2360
		8.8	32.9	15.0	98.3		149	6764	5203
9.00-20	7.0	269	1036	472	3098	16	10	6175	4750
		10.6	40.8	18.6	122.0		145	13614	10472
10.00-20 (HD)	7.5	284	1074	487	3212	18	10	6890	5300
		11.2	42.3	19.2	126.5		145	15190	11685
12.00-20 (HD)	8.5	315	1146	517	3427	20	10	9230	7100
		12.4	45.1	20.4	134.9		145	20349	15653

Note: HD – Heavy Duty

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

