

PRODUCT DATA SHEET

HRB 210

Tyre Construction: Bias

Type: Tube Less

Main Applications: Harvester

TRA Code: R-1



Salient Features:

23° Angle Lug Design:

- Stubble Resistant Design.
- Designed For High Load Carrying Applications.

Wider Lugs:

- Provides Optimum traction.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR, LI&SI	Inflation Pressure	Recommended load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm	mm	Mixed application								
		inch	inch	mm	mm		inch	inch	bar	Static	10	20
23.1-26	DW20B	587	1605	720	4800	16PR	0.8	5430	3300	2830	2530	2360
							12	11960	7270	6230	5570	5200
							1.2	6880	4190	3590	3200	2990
							17	15150	9230	7910	7050	6590
		23.1	63.2	28.3	189.0	159 A6	1.8	8720	5310	4550	4060	3790
							26	19210	11700	10020	8940	8350
							2.3	10060	6130	5250	4680	4375
							33	22160	13500	11560	10310	9640
30.5L-32	DH27B	775	1845	832	5518	18PR	0.8	7840	4770	4090	3650	3410
							12	17270	10510	9010	8040	7510
							1.2	9940	6050	5180	4620	4320
							17	21890	13330	11410	10180	9520
		30.5	72.6	32.8	217.2	170 A6	1.7	12190	7420	6360	5670	5300
							25	26850	16340	14010	12490	11670
							2.1	13800	8400	7200	6420	6000
							30	30400	18500	15860	14140	13220

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com