

PRODUCT DATA SHEET

HRR 200

Tyre Construction: Radial

Type: Tube Less

Main Applications: Harvester

TRA Code: R-1



Salient Features:

- Pattern optimised for **quiet running**.
- Optimized carcass for **better operational stability, roadability, and manoeuvring**.
- Specially designed for **high load carrying capacity**.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm	mm	Harvester Application				High Torque	Cyclic Application					
		inch	inch	10	15			25	30	40	10	10		
		bar	psi	6	9	16	19	25	6	6				
620/75R26 (SB)	DW20B	625	1590	714	4755	167 A8	1.6	5850	5230	4630	4170	3900	4170	---
							23	12890	11520	10200	9190	8590	9190	
							2	6420	5740	5080	4580	4280	4580	
							29	14140	12640	11190	10090	9430	10090	
							2.4	6840	6110	5420	4880	4560	4880	
		35	15070	13460	11940		10750	10040	10750					
		2.8	7490	6690	5930		5340	4990	5340					
		41	16500	14740	13060		11760	10990	11760					
		3.2	8180	7300	6470		5830	5450	5830					
		46	18020	16080	14250		12840	12000	12840					
4	---	---	---	---	---	---	---	9270						
58	---	---	---	---	---	---	---	20420						
650/75R32 (SB)	DW21B	655	1789	809	5351	172 A8	1.6	6870	6140	5440	4900	4580	4900	---
							23	15130	13520	11980	10790	10090	10790	
							2	7530	6730	5960	5370	5020	5370	
							29	16590	14820	13130	11830	11060	11830	
							2.4	8030	7170	6350	5720	5350	5720	
		35	17690	15790	13990		12600	11780	12600					
		2.8	8790	7850	6960		6270	5860	6270					
		41	19360	17290	15330		13810	12910	13810					
		3.2	9450	8440	7480		6740	6300	6740					
		46	20810	18590	16480		14850	13880	14850					
4	---	---	---	---	---	---	---	10710						
58	---	---	---	---	---	---	---	23590						
800/65R32 (SB)	DW27B	818	1853	835	5542	181 A8	2	8750	7810	6930	6240	5830	6240	---
							29	19270	17200	15260	13740	12840	13740	
							2.4	9450	8440	7480	6740	6300	6740	
							35	20810	18590	16480	14850	13880	14850	
							2.8	10340	9230	8180	7370	6890	7370	
		41	22780	20330	18020		16230	15180	16230					
		3.2	11150	9960	8820		7950	7430	7950					
		46	24560	21940	19430		17510	16370	17510					
		3.6	12380	11060	9800		8830	8250	8830					
		52	27270	24360	21590		19450	18170	19450					
4.5	---	---	---	---	---	---	---	14030						
65	---	---	---	---	---	---	---	30900						

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)								
		SW	OD					Speed, km/h (mph)							High Torque	Cyclic Application
								Harvester Application								
								bar	10	15	25	30	40	65		
mm	mm	mm	mm	psi	6	9	16	19	25	40	6	6				
inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch			
900/60R32 (SB)	DW28B	896	1893	852	5662	191 D	2.8	11580	10340	9150	8880	8450	7720	8880	---	
							41	25510	22780	20150	19560	18610	17000	19560		
							3.2	12480	11150	9860	9570	9110	8320	9570		
							46	27490	24560	21720	21080	20070	18330	21080		
							3.6	13290	11870	10500	10190	9700	8860	10190		
							52	29270	26150	23130	22440	21370	19520	22440		
	35.3	74.5	33.5	222.9	4		14000	12500	11060	10730	10220	9330	10730			
					58		30840	27530	24360	23630	22510	20550	23630			
					4.4		16350	14610	12920	12540	11940	10900	12540			
					64		36010	32180	28460	27620	26300	24010	27620			
					5.5		---	---	---	---	---	---	---	18530		
					80		---	---	---	---	---	---	---	40810		

Note: SB - Steel Belted

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

