

PRODUCT DATA SHEET

IMB 163

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements

TRA Code: I-1



Salient Features:

Specially Designed Ribbed Tyre:

- Low rolling resistance.

Wider Centre Rib:

- Provides excellent manoeuvrability and long tyre life.

Constant Tension Construction Minimises Crowning of the Tyre.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI/SI or PR	Inflation Pressure	Recommend Load, Kg (lbs)		
		SW	OD					Speed, Km/h (mph)		
		mm	mm				mm	mm	Bar	50
		inch	inch				inch	inch	Psi	31
9.5L-14 SL	8.00	241	741	337	2217	8 PR 111 B	3	1090		
		9.5	29.2	13.3	87.3		44	2400		
6.70-15 SL	4.5KB	170	705	324	2108	6PR 97 B	3	730		
		6.7	27.8	12.8	83.0		44	1600		
7.60-15 SL	6.00	193	734	337	2196	10 PR 110 B	4.3	1060		
		7.6	28.9	13.3	86.5		62	2330		
9.5L-15SL	7.00	241	767	350	2294	8 PR 112 B	3	1120		
		9.5	30.2	13.8	90.3		44	2470		
		241	767	350	2294	12 PR 121 B	4.4	1450		
		9.5	30.2	13.8	90.3		64	3200		
11L-15SL	8.00	279	777	354	2323	8 PR 113 B	2.5	1150		
		11.0	30.6	13.9	91.5		36	2540		
		279	777	354	2323	12 PR 121 B	3.6	1450		
		11.0	30.6	13.9	91.5		52	3200		
12.5L-15SL	10.00	318	823	373	2462	12 PR 127 B	3.6	1750		
		12.5	32.4	14.7	96.9		52	3860		
12.5L-16SL	10.00	318	848	386	2537	14 PR 130 B	3.9	1900		
		12.5	33.4	15.2	99.9		56	4180		
16.5L-16.1 -i1	14.00	419	1024	459	3063	12 PR 138 B	2.5	2360		
		16.5	40.3	18.1	120.6		36	5200		
21.5L-16.1 -i1	18.00	546	1130	502	3380	10 PR 146B	1.9	3000		
		21.5	44.5	19.8	133.1		28	6610		

Note: SL – Standard Load

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

