

# PRODUCT DATA SHEET

## IMB 164

**Tyre Construction:** Bias

**Type:** Tube Less / Tube Tyre

**Main Applications:** Implements

**TRA Code:** IMP



### *Salient Features:*

**Specially designed Rib Pattern:**

- Ensures soil protection.
- Suitable for both On Road and Off-Road applications.
- Built for carrying high loads.



# Technical Data



Size	Recommended Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	PR, LI&SI	Inflated Pressure	Recommend load, kg (lbs)			
		SW	OD					Speed, km/h (mph)			
		mm	mm	mm	mm		Free rolling				
		inch	inch	inch	inch		bar	10	25	30	40
						psi	6	16	19	25	
200/60-14.5	AG 6.75	205	608	283	1818	10PR 106 A8	3.7	1110	940	880	790
							54	2442	2068	1936	1738
							4.1	1180	1000	940	840
							59	2596	2200	2068	1848
		8.1	23.9	11.1	71.6		4.5	1250	1060	1000	890
							65	2750	2332	2200	1958
							5	1330	1130	1060	950
							73	2926	2486	2332	2090
200/60-14.5	AG 6.75	205	608	283	1818	14PR 113 A8	5.2	1360	1150	1090	970
							75	2992	2530	2398	2134
							5.7	1430	1210	1140	1020
							83	3146	2662	2508	2244
		8.1	23.9	11.1	71.6		6.3	1510	1290	1210	1080
							91	3322	2838	2662	2376
							7	1610	1370	1290	1150
							102	3542	3014	2838	2530
250/65-14.5	AG 8.00	251	694	318	2076	12PR 119 A8	3.6	1620	1380	1300	1160
							52	3564	3036	2860	2552
							3.9	1710	1450	1370	1220
							57	3762	3190	3014	2684
		9.9	27.3	12.5	81.7		4.3	1810	1540	1440	1290
							62	3982	3388	3168	2838
							4.7	1900	1620	1520	1360
							68	4180	3564	3344	2992

Note: All tyres confirm to ETRTO standards

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

