

PRODUCT DATA SHEET

IMR 140

Tyre Construction: Radial

Type: Tube Less

Main Applications: Implements

TRA Code: IMP



Salient Features:

- Optimized tread design with improved lateral traction for **better operational stability on inclined surfaces and self-cleaning.**
- Longer cleat length give **low soil compaction, better traction,** and **higher stability.**
- Better suitability for **grass land, garden & tillage operations.**



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)
		SW	OD					Speed, km/h (mph)
		mm	mm					50
		inch	inch					31
31X15.50R15	13LB	391	792	360	2369	122 B	2.8	1500
		15.4	31.2	14.2	93.3		41	3300
33X15.50R15	13LB	391	843	381	2521	126 B	3.2	1700
		15.4	33.2	15.0	99.3		46	3740

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm	mm					Mixed application						
		inch	inch					Static	10	25	30	40	50	65
425/55R17	13.00	425	881	401	2635	134 D	2	3130	2450	2150	2050	1850	1650	1360
							29	6890	5400	4740	4520	4070	3630	3000
							2.4	3610	2830	2480	2370	2140	1900	1570
							35	7950	6230	5460	5220	4710	4190	3460
							2.8	4090	3200	2810	2690	2420	2150	1780
		41	9010	7050	6190		5930	5330	4740	3920				
		3.2	4510	3530	3100		2960	2670	2370	1960				
		46	9930	7780	6830		6520	5880	5220	4320				
		3.5	4880	3820	3350		3200	2880	2570	2120				
		51	10750	8410	7380		7050	6340	5660	4670				
500/50R17 (SB)	16.00	503	932	422	2787	145 D	2.4	4440	3470	3050	2910	2620	2340	1930
							35	9780	7640	6720	6410	5770	5150	4250
							2.8	5040	3940	3460	3310	2980	2650	2190
							41	11100	8680	7620	7290	6560	5840	4820
							3.2	5540	4340	3810	3640	3280	2920	2410
		46	12200	9560	8390		8020	7220	6430	5310				
		3.6	6070	4750	4170		3990	3590	3190	2640				
		52	13370	10460	9190		8790	7910	7030	5810				
		4	6670	5220	4580		4380	3940	3510	2900				
		58	14690	11500	10090		9650	8680	7730	6390				

Note: SB - Steel Belted

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

