

# PRODUCT DATA SHEET

## IRB 260

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Irrigators, Pivot

**TRA Code:** R-1



### *Salient Features:*

**Specially Designed Tread Pattern:**

- Excellent traction and outstanding self-cleaning properties.

**Robust Nylon Carcass Construction:**

- Enhances its ability to carry continuous heavy loads.

**Special Tread Compound:**

- Minimizes wear and extends tyre life significantly.



# Technical Data



Size	Recom. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
								Field operation			Road Operation; Not high and Sustained Torque						
								High Torque	Low Torque								
		mm	mm					mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					
bar	10	10	20	Static													
psi	6	6	12					6	16	20	25						
11.2-38	W10	284	1459	687	4364	6PR	1.5	1130	1590	1300	2440	1590	1300	1130	1060		
							22	2490	3500	2860	5370	3500	2860	2490	2330		
		11.2	57.4	27.0	171.8		114 A8	1.6	1180	1650	1350	2530	1650	1350	1180	1100	
								23	2600	3630	2970	5570	3630	2970	2600	2420	
	14.9-24	W13	378	1252	570	3745	8PR	1.7	1220	1710	1400	2620	1710	1400	1220	1140	
								25	2690	3770	3080	5770	3770	3080	2690	2510	
			14.9	49.3	22.4	147.4		128 A8	1.8	1260	1770	1450	2710	1770	1450	1260	1180
									26	2780	3900	3190	5970	3900	3190	2780	2600
11.2-24	W10	284	1103	509	3299	6PR	1.5	1730	2430	1990	3730	2430	1990	1730	1620		
							22	3810	5350	4380	8220	5350	4380	3810	3570		
		11.2	43.4	20.0	129.9		110 A8	1.6	1800	2520	2070	3860	2520	2070	1800	1680	
								23	3960	5550	4560	8500	5550	4560	3960	3700	
	11.2-24	W10	284	1103	509	3299	6PR	1.7	1860	2610	2140	4000	2610	2140	1860	1740	
								25	4100	5750	4710	8810	5750	4710	4100	3830	
			11.2	43.4	20.0	129.9		110 A8	1.8	1930	2700	2210	4140	2700	2210	1930	1800
									26	4250	5950	4870	9120	5950	4870	4250	3960
11.2-24	W10	284	1103	509	3299	6PR	1.5	1020	1430	1170	2190	1430	1170	1020	950		
							22	2250	3150	2580	4820	3150	2580	2250	2090		
		11.2	43.4	20.0	129.9		110 A8	1.6	1060	1490	1220	2280	1490	1220	1060	990	
								23	2330	3280	2690	5020	3280	2690	2330	2180	
11.2-24	W10	284	1103	509	3299	6PR	1.7	1100	1550	1270	2370	1550	1270	1100	1030		
							25	2420	3410	2800	5220	3410	2800	2420	2270		
		11.2	43.4	20.0	129.9		110 A8	1.8	1130	1590	1300	2440	1590	1300	1130	1060	
								26	2490	3500	2860	5370	3500	2860	2490	2330	

Note: All tyres confirm to ETRTO standards

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

