

PRODUCT DATA SHEET

LSB 780

Tyre Construction: Bias

Type: Tube Less

Main Applications: Log Skidder

TRA Code: LS-2



Salient Features:

- Robust Lug Design Uncompromising tread design for **excellent self-cleaning and longer tread life.**
- Optimized Lateral stiffness provides **better steer control and maneuverability on wet and dry surfaces.**
- Reinforced carcass & shoulder areas with special compound for **protection from frequent puncture & cut:**



Technical Data



Size	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommended load (kg) (lbs)					
		SW	OD					Speed (kmph) (mph)					
								Log Skidder Application					
								bar	Static	15	25	30	40
psi	9	16	19	25									
28L-26 SB & DB	DW25B	714	1644	736	4917	20PR 165 A6	1.2	9260	4120	3770	3430	3090	
							17	20400	9070	8300	7560	6810	
							1.6	10960	4870	4470	4060	3650	
							23	24140	10730	9850	8940	8040	
		28.1	64.7	29.0	193.6		2.0	12500	5560	5090	4630	4170	
							29	27530	12250	11210	10200	9190	
							2.4	13910	6180	5670	5150	4635	
							35	30640	13610	12490	11340	10210	
30.5L-32 SB & DB	DH27	775	1847	833	5524	26PR 176 A6	1.2	11800	5240	4810	4370	3930	
							17	25990	11540	10590	9630	8660	
							1.6	13960	6200	5690	5170	4650	
							23	30750	13660	12530	11390	10240	
		30.5	72.7	32.8	217.5		2.0	15900	7070	6480	5890	5300	
							29	35020	15570	14270	12970	11670	
							2.8	19170	8520	7810	7100	6390	
							40	42220	18770	17200	15640	14070	
30.5L-32 SB & DB	DH27	775	1847	833	5524	32PR 180 A6	2.4	17630	7840	7180	6530	5880	
							35	38830	17270	15810	14380	12950	
							2.8	19310	8580	7870	7150	6440	
							41	42530	18900	17330	15750	14190	
		30.5	72.7	32.8	217.5		3.0	20090	8930	8180	7440	6700	
							44	44250	19670	18020	16390	14760	
							3.4	21600	9600	8800	8000	7200	
							49	47580	21150	19380	17620	15860	

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Size	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommended load (kg) (lbs)						
		SW	OD					Speed (kmph) (mph)						
								Cable/Grapple Skidder	Log Skidder Application					
									Static	15	25	30	40	
mm	mm	mm	mm	bar	10	9	16	19	25					
inch	inch	inch	inch	psi	6	9	16	19	25					
23.1-26 SB	DW20B	587	1632	731	4881	16PR 160 A6 172 A2	1.2	-	8100	3600	3300	3000	2700	
							17	-	17840	7930	7270	6610	5950	
							1.6	-	9590	4260	3910	3550	3200	
							23	-	21120	9380	8610	7820	7050	
							2.0	-	10910	4850	4440	4040	3640	
		29	-	24030	10680		9780	8900	8020					
		2.4	-	12150	5400		4950	4500	4050					
		35	-	26760	11890		10900	9910	8920					
		2.8	6300	-	-		-	-	-					
		41	13880	-	-		-	-	-					

Note: SB-Steel Belted DB-Dual Bead

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

