

# PRODUCT DATA SHEET

## MPR 390

**Tyre Construction:** Radial

**Type:** Tube Less

**Main Applications:** Trailer

**TRA Code:** MPT



### *Salient Features:*

- Optimized Tread Design provides **quite run at high speeds.**
- Carcass optimised for **better ride comfort.**
- Tread design optimised for **better mileage and fuel efficiency.**



# Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR, LI&SI	Inflation Pressure	Recommended load, kg (lbs)								
		SW	OD					Speed, km/h (mph)								
		mm	mm					Mixed application								
		inch	inch					15	20	30	40	50	65	80	90	100
		mm	mm	mm	mm	bar	9	12	19	25	31	40	50	56	62	
		inch	inch	inch	inch	psi	9	12	19	25	31	40	50	56	62	
355/60R18 (SB)	11	353	883	404	2641	16PR	6	4370	3980	3310	3050	2970	2880	2760	2700	2650
		13.9	34.8	15.9	104.0	142 J	87	9630	8770	7290	6720	6540	6340	6080	5950	5840

Note: SB - Steel Belted

Note: All tyres confirm to ETRTO standards

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

