



SSB 330

Product Data Sheet

Marketing Department.
September 23, 2020

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com

Release Month: September'20

Brand: ASCENSO

Tread Pattern : SSB 330

Tyre Construction : Bias

Type : Tubeless

Main Applications: Skid Steer

TRA Code : R-4

List of Sizes

Size	PR
10-16.5	8,12
12-16.5	10,12



Salient Features

Solid Centre Lug:

Provide wide contact and stability

Open Shoulder Design:

Increases traction on loose off-road surfaces



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)	
		SW	OD					Speed, km/h(mph)	
		mm	mm					Mixed Application	
		In	in				mm	in	Bar
								Psi	7
10-16.5	8.25	264 10.4	773 30.4	356 14.0	2312 91.0	8PR 130A2	4.1	1880	
							60	4140	
						10PR 134A2	5.2	2140	
							75	4710	
12-16.5	9.75	307 12.1	831 32.7	380 15.0	2486 97.9	10 PR 140A2	4.5	2550	
							65	5600	
						12PR 145A2	5.5	2900	
							80	6393	

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover