



SSB 333

Product Release Document

Marketing Department.

6 Oct, 2021

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com

Release Month: Oct'22

Brand: ASCENSO

Tread Pattern : SSB 333

Tyre Construction: Bias

Type : Tubeless

Main Applications: Skid Steer Loader

TRA Code : NHS

List of Sizes

Size	PR
10-16.5	10
12-16.5	12



Salient Features

- High tread depth, broad lugs and special compound
 - Makes it optimal for usage on hard & rough surfaces
- Robust Casing
 - Provides high durability with protection against punctures and damages
- Rim Guard
 - Protects the rim flange area against flats and wheel damage



Technical Specification

Size	Rim	Unloaded		Loaded	Rolling	Load	Recommended		
		dimension		Static	Circum	Index	Load	Infl.	Speed
		SW	OD	Radius				press.	
		mm	mm	mm	mm	Speed	Kg	bar	Km/h
in	in	in	in	Symbol	lbs	psi	mph		
10-16.5	8.25	264	773	356	2312	10PR 134 A2	2130	5.2	10
		10.4	30.4	14.0	91.0		4675	75	6
12-16.5	9.75	318	835	381	2497	12PR 145 A2	2900	5.5	10
		12.5	32.9	15.0	98.3		6390	80	6

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com