

PRODUCT DATA SHEET

SPB 260

Tyre Construction: Bias

Type: Tube Less

Main Applications: Sugarcane Trailer

TRA Code: R-3



Salient Features:

Large Tread Area:

- Increases flotation and minimises ground disturbance in soil.

Optimized Diamond Lug Pattern with Sipes:

- Reduces groove cracks and minimises slippage, enhances productivity.

Heavy Under Tread:

- Ensures puncture and impact resistance, thereby reducing downtime.



Technical Data



Size	Rim	Unloaded Dimensions		Static Load Radius	Rolling Circumference	PR, LI&SI	Inflation Pressure	Recommended Load kg (lbs)
		SW	OD					Speed kmph, (mph)
		mm	mm					40
		inch	inch					25
23.1-26 (DB)	DW20B	587	1581	710	4748	18PR 170 A8	2.6	6000
		23.1	62.2	28.0	186.9		38	13220

Size	Rim	Unloaded Dimensions		Static Load Radius	Rolling Circumference	PR, LI&SI	Inflation Pressure	Recommended Load kg (lbs)
		SW	OD					Speed kmph, (mph)
		mm	mm					30
		inch	inch					19
620/75-30 (23.1-30) (DB)	DW20A	605	1675	758	5010	16PR 161 A6	2.3	4625
	DW20B	23.8	65.9	29.8	197.2		33	10190
650/75-32 (24.5-32) (DB)	DH21	625	1755	795	5249	16PR 164 A6	2.1	5000
	DH21B	24.6	69.1	31.3	206.7		30	11010
650/75-32 (24.5-32) (DB)	DH21	625	1755	795	5249	18PR 167 A6	2.4	5450
	DH21B	24.6	69.1	31.3	206.7		35	12000

Note: DB – Dual Bead

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

