

# PRODUCT DATA SHEET

## TGB 610

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Grader

**TRA Code:** G-2



### *Salient Features:*

**Open Tread Design:**

Optimum traction on soil, sand, rock, and gravel.

**Reinforced Carcass:**

Withstands grading operation.

**Abrasion Resistant Tread Compound:**

Ensures longer service life and low operating cost.



# Technical Data



Size	Recomm. Rim	Alternate Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)
			SW	OD					Speed (kmph) (mph)
			mm	mm					10
			inch	inch					6
13.00-24	8	9.00/1.5 DC, 10.00/VA (SDC)	333	1278	581	3823	12 PR	3	2725
			13.1	50.3	22.8	150.5	143 A8	44	5995
13.00-24	8	9.00/1.5 DC, 10.00/VA (SDC)	333	1278	581	3823	16 PR	4	3250
			13.1	50.3	22.8	150.5	149A8	59	7150
14.00-24	8	10.00/VA (SDC), 10.00 WA (SDC)	362	1348	610	4032	12 PR	2.8	3075
			14.2	53	24	158.7	147 A8	40	6765
14.00-24	8	9.00/1.5(DC), 10.00/VA(SDC)	362	1348	610	4032	16 PR	3.8	3650
			14.2	53	24	158.7	153 A8	55	8030

**Note: All tyres confirm to ETRTO standards**

## Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

