

# PRODUCT DATA SHEET

## THB 230

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Telehandler

**TRA Code:** R-4



### *Salient Features:*

**Specially Designed Directional Tread Pattern:**

- Ensures traction & self-cleaning properties.
- Provides excellent stability during vehicle operation.

**Strong Nylon Carcass:**

- Safeguards the tyre against failures.



# Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR / LI&SI	Inflation Pressure	Recommended Load kg, (lbs)		
		SW	OD					Speed kmph (mph)		
		mm	mm				mm	mm	bar	40
		inch	inch				inch	inch	psi	25
15.5/80-24 (400/80-24)	W12	394	1266	576	3787	12PR	3	4125		
		15.5	49.8	22.7	149.1	157 A8	44	9100		
15.5/80-24 (400/80-24)	W12	394	1266	576	3787	16PR	4	4875		
		15.5	49.8	22.7	149.1	163 A8	59	10725		

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR / LI&SI	Inflation Pressure	Recommended Load kg, (lbs)		
		SW	OD					Speed kmph (mph)		
		mm	mm				mm	mm	bar	50
		inch	inch				inch	inch	psi	31
405/70-24 (16.0/70-24)	13	418	1177	539	3521	14PR	3.5	3550		
		16.5	46.3	21.2	138.6	152 B	51	7810		
405/70-20 (16.0/70-20)	13	418	1075	488	3216	14PR	3.5	3250		
		16.5	42.3	19.2	126.6	149 B	51	7150		

Note: All tyres confirm to ETRTO standards

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

