

# PRODUCT DATA SHEET

## WLB 550

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Wheel Loader

**TRA Code:** E-3/L-3



### *Salient Features:*

**Robust Tread Design:**

Generates maximum traction and resistance to slippage.

**Strong Nylon Casing:**

- Heavy load-carrying capacity
- Resistance to impacts.



# Technical Data



Size	Recomm. Rim	Alternate Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)			
			SW	OD					Speed (kmph) (mph)			
			mm	mm					mm	mm	bar	10
			inch	inch					inch	inch	psi	6
15.5-25	12.00/1.3		394	1278	583	3838	12 PR	4	5600			
			15.5	50.3	22.9	151.1	168 A2	58	12350			
17.5-25	14.00/1.5	14.00/1.5D 14.00/1.3DC, 13.00/1.4 DC	445	1348	612	4032	16 PR	4.8	7300			
			17.5	53.1	24.1	158.7	177 A2	69	16060			
17.5-25	14.00/1.5	-	445	1348	612	4032	20 PR	5.8	8250			
			17.5	53.1	24.1	158.7	181 A2	84	18150			
17.5-25	14.00/1.5	-	445	1348	612	4032	24 PR	7	10000			
			17.5	53.1	24.1	158.7	188 A2	102	22000			
20.5-25	17.00/2.0	17.00/1.7	520	1492	672	4463	16 PR	3.5	8250			
			20.4	58.7	26.4	175.7	181 A2	51	18150			
20.5-25	17.00/2.0	17.00/1.7	520	1492	672	4463	20 PR	4.5	9500			
			20.4	58.7	26.4	175.7	186 A2	66	20900			
23.5-25*	19.5/1.5	19.5/2.5	597	1617	723	4837	20 PR	3.8	10900			
			23.5	63.7	28.5	190.4	191 A2	55	23980			
26.5-25*	22.0/3.0		673	1750	777	5234	28 PR	4.8	15500			
			26.5	68.9	30.6	206.1	203 A2	69	34100			

Note: Sizes marked in \* are L-3.

**Note: All tyres confirm to ETRTO standards**

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

