

PRODUCT DATA SHEET

BOSS TD 16

Tyre Construction: Bias

Type: Tube Type

Main Applications: Tractor

TRA Code: R-1



Salient Features:

Dual-Lug Angle Design with High inner volume:

- Excellent Self-Cleaning Properties.
- Excellent Traction.

Centre Tie bar with Strong Lug Base:

- Minimizes lug shuffling in operation.

Superior Nylon Construction:

- High load carrying capacity.

Deep Tread:

- Improved Mileage.
- Enhanced Performance in both Field and Haulage

CCR (Cut & Chip Resistance) Compound:

- Resistance to Cut & Chip & also minimizes Puncture.



Technical Data



| Tyre Size | PR | TT/TL | LI/SI | Recomm. Rim | Unloaded Inflated Dimension | | Static Loaded Radius | Rolling Circumference | Max Speed | Load Carrying Capacity | | | |
|-----------|----|-------|--------|----------------|-----------------------------|------|----------------------|-----------------------|-----------|------------------------|-----------|-----|-----|
| | | | | | SW | OD | | | | Inflation Pressure | Max. Load | | |
| | | | | | mm | mm | | | | | | bar | kg |
| | | | | | inch | inch | | | | | | psi | lbs |
| 13.6-28 | 12 | TT | 128 A6 | W12 | 360 | 1340 | 603 | 3918 | 30 | 2.3 | 1800 | | |
| | | | | | 14.2 | 52.8 | 23.7 | 154.2 | 19 | 33 | 3960 | | |
| 14.9-28 | 12 | TT | 134 A6 | W13 | 388 | 1380 | 625 | 4082 | 30 | 2.3 | 2120 | | |
| | | | | | 15.3 | 54.3 | 24.6 | 160.7 | 19 | 33 | 4670 | | |

Note: All tyres confirm to ETRTO standards.

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com