

PRODUCT DATA SHEET

SSS 340

Tyre Construction: Solid

Type: -

Main Applications: Skid Steer

TRA Code: -



Salient Features:

Deep, Stepped Block Tread for Superior Traction:

High-void, self-cleaning tread blocks maintain consistent grip by ejecting debris, ensuring dependable off-road traction in waste, recycling, and construction environments

Optimized Aperture Design for Comfort & Cooling:

Engineered sidewall apertures absorb shocks and disperse heat, delivering a smoother ride and reducing heat-related cracking during long, continuous operations

Severe-Duty Solid Rubber Construction:

Premium solid compound resists cuts, chunking, and abrasion, offering longer tyre life and reliable performance in aggressive, high-impact work sites



Technical Data



Size	Rim	Tyre Dimensions		Tyre Load Capacity (kgs)					
		SW	OD	Static	Counterbalanced lift trucks		Other Vehicles		
					Load Wheel	Steering Wheel			
					25 kmph	25 kmph	6 kmph	10 kmph	25 kmph
		mm	mm		16 mph	16 mph	4 mph	6 mph	16 mph
31x10-20	7.50	237	781	4680	4030	3100	4030	3660	3100
		9.3	30.7	10350	8885	6835	8900	8100	6850
33x12-20	7.50	287	831	6040	5200	4000	5200	4720	4000
		11.3	32.7	13350	11465	8820	11500	10400	8850

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com