

BHB 316 - Data Sheet

Industrial & Construction | Bias | R-4 | TL | 5 Years

Salient Features & Benefits

BHB 316 – Engineered for Backhoe Loader Dig & Load Operations

Wider lug width

- Provides Better stability ,Higher load carrying capacity and maximum footprint area

Super cut resistance Tread Compound

- Specially formulated compound resists cuts, chunks, and abrasion encountered at construction and agricultural sites, extending tyre service life.

Reinforced Lug Tread Design

- Wide, robust lugs improve surface contact and withstand harsh digging and loading conditions, supporting consistent performance across mixed terrains.

Deep Grooved, Self-Cleaning Tread Geometry

- Efficient groove layout enables quick evacuation of mud and debris, maintaining performance and reducing downtime in wet or loose underfoot conditions.

Strong Carcass Construction

- Durable casing structure enhances load-carrying capability and structural stability, ensuring reliability through repeated digging and loading cycles.



Machineries



Backhoe Loader

Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
-	18.4-26	DW16A	-	16PR 160A8	467	1425	646	4262	TL
-	16.9-28	W15L	-	14PR 156A8	429	1410	644	4217	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.