

ELTY 4310 - Data Sheet

Earth Mover | All Steel Radial | E-4 | TL | 5 Years



Salient Features & Benefits

ELTY 4310, Engineered for excellence in Loading & Haulage Applications

Deep Multi-Block Tread Design

- Optimized multi-block tread provides superior traction across harsh haul road conditions.
- Wider footprint enhances stability and reduces vibrations.

Stepped Centre Block Design protecting the tread

- Reinforced stepped centre blocks reduce stress and tread cracking.
- Prevents stone entrapment for improved tyre durability.

Trapezoidal grooves to remove debris from tyre

- Angled groove walls creating a wider opening towards outside making it easy for debris to fall out naturally as the tyre rotates

Robust Shoulder Design for Harsh Conditions

- Resists shoulder chunking and maintains tread integrity.
- Sustains traction throughout the tyre's service life

Tread compound to suit operational requirement

- Cut- and wear-resistant compound options for varied applications.
- Optimized casing and compound control heat build-up and enhance TKPH performance.

Machineries



Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
-	23.5R25 (CR)	19.5/2.5	-	185 B	597	1609	719	4812	TL
-	26.5R25 (CR)	22.00/3.0	-	193 B	673	1741	774	5207	TL
-	29.5R25 (CR)	25.00/3.5	-	200B	750	1863	824	5572	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.