

FFB 841 - Data Sheet

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

Forestry forwarder Bias 841 Engineered for advanced forestry applications which is Track tyre for harvesters and forwarders



Track Compatibility with High Stability

- Superior tread geometry with inter-lug terraces & centre tie bar
- Provides excellent grip and stability even with track usage; minimises lug movement for smooth operation

Exceptional Puncture Resistance

- Reinforced steel-belted carcass with protective forestry compound
- Protects against sharp stumps, stones, and reduces downtime in harsh forestry environments

Heavy Load Handling

- Robust sidewall equipped with strong lug base and reinforced bead zone
- Withstands heavy loads and prevents rim slippage

Strong Lug Base:

- Design with Centre Tie Bar.
- Minimizes lug shuffling in operation.

Machineries



Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
E11*106R00/20*106 83*00	710/40-22.5 (SB)	AG24.00	-	24PR 167A8	709	1167	531	3504	TL
E11*106R00/21*106 79*00	710/40-24.5 (SB)	AG24.00	-	24PR 168 A8	699	1230	562	3694	TL
E11*106R00/20*106 76*00	600/55-26.5 (SB)	AG20.00	-	20PR 165 A8	605	1342	612	4030	TL
E11*106R00/21*106 77*00	710/45-26.5 (SB)	AG24.00	-	20PR 168 A8	705	1345	614	4039	TL
E11*106R00/20*106 78*00	710/45-26.5 (SB)	AG24.00	-	24PR 173 A8	705	1345	614	4039	TL
-	750/55-26.5 (SB)	AG24.00	-	26PR 185 A8	769	1473	667	4423	TL
E11*106R00/21*106 80*00	710/55-28.5 (SB)	AG24.00	-	24PR 180 A8	719	1515	688	4549	TL
E11*106R00/21*106 82*00	780/50-28.5 (SB)	AG26.00	-	26PR 185 A8	783	1515	688	4549	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.