

FFB 842 - Data Sheet

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

Forestry forwarder Bias 842 which is Traction tyre for harvesters and forwarders

High Traction:

- Optimized lug angle with extensive inter-lug space.
- Provides excellent traction in operation & Better Self-cleaning.

Less Breakdown in severe forest application

- Protective forestry compound
- Resistance from frequent punctures & cuts.

Outstanding stability

- Strong Casing with High Performance Steel belts.
- Less impact and fatigue failure with High load carrying capacity

Fuel Efficiency and Reduced Vibration

- Dense Tread Mass with Improved Lug Overlap.
- Minimizes vibration for superior ride comfort while improving

Exceptional Puncture Resistance:

- Reinforced steel-belted carcass with protective forestry compound
- Protects against sharp stumps, stones, and reduces downtime in harsh forestry environments.



Machineries



Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
E11*106R00/21*11 813*00	500/60-22.5 (SB)	16.00DC	-	20 PR 156A8/163A2	503	1172	533.5	3519.4	TL
E11*106R00/21*11 814*00	550/60-22.5 (SB)	16.00DC	-	18 PR 157A8/164A2	553	1240	561.5	3723.6	TL
E11*106R00/21*11 695*00	800/45-30.5 (SB)	AG28.00	-	20PR 174A8/181A2	800	1505	689	4519	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.