

FFB 843 - Data Sheet

Forestry | Bias | LS-2 | TL | 5 Years

Salient Features & Benefits

FFB 843- High Flotation Design with Enhanced Strength & Field Protection

Flotation Tread Design:

- Excellent Traction.
- Better Self Cleaning.

Strong Nylon Carcass:

- High Load Carrying Capacity.

Overlap of lugs at centre:

- Provided good Roadability.
- Low Tread wear.
- Smooth Ride.

Optimized Bead Area:

- Minimizes Bead failure in operation.
- Ease of mounting.
- Resistance to Rim slip.

SSR compound (Special Stubble Resistant):

- Longer Tire Life and defense against stubble which provides better protection on field.

Reinforced Steel belts:

- Increased resistance to punctures and a high carrying capacity.



Machineries



Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
E11*106R00/21*10864*00	400/60-15.5 (SB)	AG 13.00	-	20 PR 152 A8 / 148 B FR 140 A8 / 135 B DW	404	874	395	2625	TL
-	400/60-22.5 (SB)	13	-	20 PR FR-163 A8 159 B DW-151 A8 147 B	407	1070	491.4	3213.1	TL
E11*106R00/21*11847*00	500/45-22.5 (SB)	16	-	16 PR FR-154 A8 150 B DW-142 A8 138 B	503	1022	471.6	3069	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.