

FTR 176 - Data Sheet

Agriculture | Radial | IMP | TL | 7 Years



Salient Features & Benefits

Flotation Radial 176, specially designed for High-Speed farm & trailer application.

Enhanced Roadability

- Non-Directional Block tread design
- Provides excellent traction in mixed application while minimizing vibration at roading speed.

Less Vibration & Low tyre Noise

- High Rubber to Void ratio.
- Enhanced drive comfort and less drive fatigue.

Durability and Strength

- Strong Radial Casing with High Performance Steel belts
- Steel-belt structure improves puncture resistance & Less impact with High load carrying capacity.


Reduced Soil Compaction

- Large contact patch with Open Tread Design with Solid Rounded Shoulder
- Offers maximum flotation and protect delicate crops and soil from damage

Lower Fuel Cost

- Low Rolling Resistance
- less fuel consumption especially at high-speed operation.

Machineries



Flotation Trailer

Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
-	560/45R22.5 (SB)	AG16.00	-	152 D/ 149 E	565	1076	488	3218	TL
-	560/60R22.5 (SB)	AG20.00	AG16.00,AG17.00,A G18.00	165D/ 162E	605	1244	563	3810	TL
E11*106R00/21*1 0824*00	560/60R22.5 (SB)	AG20.00	AG16.00,AG17.00,A G18.00	170 D/ 167 E	605	1244	563	3810	TL
-	710/65R26 (28LR26) (SB)	DW25B	-	173 D/ 170 E	715	1555	699	4651	TL
-	600/55R26.5 (SB)	AG20.00	-	173D/ 170E	612	1350	616	4038	TL
-	650/55R26.5 (SB)	AG20.00	-	178D/ 175E	665	1389	632	4154	TL
-	710/50R26.5 (SB)	AG24.00	AG20.00	179 D/ 176 E	690	1390	632	4157	TL
-	750/45R26.5 (SB)	AG24.00	-	174D/ 171E	754	1365	622	4082	TL
-	750/60R30.5 (SB)	AG24.00	-	181D/ 178E	780	1675	753	5110	TL
-	850/50R30.5 (SB)	AG28.00	-	182D/ 179E	862	1625	732	4972	TL
-	30.5LR32 (SB)	DH27B	DW27B	178 D/ 175 E	790	1800	814	5383	TL
-	900/65R32 (35.5LR32) (SB)	DW30B	-	197 D/ 194 E	917	1983	889	5931	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.