

IMB 166 - Data Sheet

Agriculture | Bias | IMP | TL | 5 Years

Salient Features & Benefits

IMB 166, specially designed for Implements

Low Soil Compaction

- Wider footprint and optimised pressure distribution
- Protects soil structure and enhances productivity in sensitive farmland

Outstanding Traction

- Directional tread pattern with robust lugs
- Delivers high grip in soft, muddy or uneven terrain

Excellent Self-Cleaning

- Wide lug spacing and open channel design
- Ejects soil and debris effectively for uninterrupted field operation

High Load Carrying Capacity

- Superior carcass with reinforced construction
- Supports very heavy loads during field and transport applications without compromising stability

Durability

- Deep tread with strong rubber compound
- Withstands harsh field usage and extends tyre service life



Machineries



Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
E11*106R00/19*81 12*00	320/60- 12	10.50 I	-	132A8 FR 120 A8 DW	324	690	311	2064	TL
E11*106R00/21*81 11*00	280/60- 15.5	AG8.00	-	128 A8 FR 116 A8 DW	272	745	342	2228	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.