

IMR 142 - Data Sheet

Agriculture | Radial | IMP | TL | 7 Years



Salient Features & Benefits

IMR 142 – Versatile Implement Tyre for Road Transport & Field Protection

Wide Footprint with Low-Pressure Design

- Distributes load evenly to minimize ground pressure, protecting grassland and soil during field and transport operations.

Balanced Tread Pattern for Multi-Surface Use

- Delivers stable and consistent performance across soil, grass, and paved roads, making it ideal for grain transport, silage, and fertilizer applications.

High-Speed Capability with Driving Comfort

- Designed for transport at operating speed up to 65km/h.

Robust Construction for Heavy Implement Loads

- Strong casing supports high load requirements of trailers, grain baggers, and forage equipment while ensuring durability and service reliability.

Machineries



Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
-	500/50R17 (SB)	16	-	149 D	503	932	422	2787	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.