

TDB 126 - Data Sheet

Agriculture | Bias | R-2 | TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 126: Built to Perform for Multiple Field Applications from Spraying/Row Crop to Puddling Operation

Narrow Section Width Design:

- Facilitates Easy Movement of Tractor with Minimum Crop Damage

Taller Overall Diameter:

- Provide Better Ground Clearance

Optimized Lug Pattern:

- Delivers Superior Traction in Wet and Soft Field Conditions

Deep Tread Depth:

- Gives Longer Tyre life and Improved Performance in Loose Soil

Optimum Lug Spacing:

- Provides Better Self-Cleaning

Strong Casing Design:

- Enhanced Resistance to Cut, Stubble Damages & Punctures

Machineries



Tractor

Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
E11*106R00/21*12 159*00	5.00-26 (120/90-26)	4JA	-	6 PR 90 A2	127	950	449.7	2841.3	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.