

VHR 3000 - Data Sheet

Agriculture | Radial | R-1/R-1W | TL | 7 Years

Salient Features & Benefits

VF Harvester Radial 3000, specially designed Ultra Modern harvester, Spreader, Grain cherts.

Improved Traction

- Dual-angle lug design.
- Less slippage

High Productivity

- Large contact surface area.
- This tyre offers max flotation and soil protection, and with rounded shoulders, helps minimize ruts.

Smooth ride

- Optimized lugs overlap in the center.
- Comfortable ride on all surfaces & reduces wear on pavement.

Higher Load-Carrying Capacity

- Advanced VF technology, Strong shoulder with a higher draft angle and base radius.
- Withstand heavy loads at low inflation pressure & Excellent for frequent loading and unloading with CFO Marking.

Durability and Strength

- High flex carcass with durable Steel belts.
- Steel Belts offer excellent puncture resistance and optimized load distribution

Longer Tyre Life


- SSR (Special Stubble Resistant) compound.
- Defence against stubble, which provides better protection on the field.




Machineries



Harvester



Spreader



Grain Cart

Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
E11*106R00/20*1 0493*00	VF 1000/50R25 CFO (SB, SG)	36.0TH	-	184 D / 184 A8	1006	1635	730	4890	TL
E11*106R00/20*1 0485*00	VF 750/50R26 CFO (SB, SG)	DW25B	DW27B	169 D / 169 A8	734	1410	639	4217	TL
E11*106R00/21*1 0888*00	VF 750/65R26 CFO (SB, SG)	DW27B	DW25B	180 A8	754	1636	733	4893	TL
-	VF 710/60R30 CFO (SB, SG)	DW25B	DW24B,DW27 B	171 D / 171 A8	708	1614	732	4827	TL
E11*106R00/21*1 0891*00	VF 800/65R32 CFO (SB, SG)	DW28B	DW27B,DW30 B	183 A8	796	1853	835	5542	TL
E11*106R00/21*1 0889*00	VF 900/60R32 CFO (SB, SG)	DW30B	-	191 A8	881	1893	852	5662	TL
E11*106R00/20*1 0491*00	VF 1050/50R32 CFO (SB, SG)	36.00VA(SDC)	-	198 D / 198 A8	1038	1863	840	5572	TL
E11*106R00/21*1 0894*00	VF 580/80R34 CFO (SB, SG)	DW20B	-	178 A8	586	1792	815	5360	TL
E11*106R00/21*1 0883*00	VF 620/70R42 CFO (SB, SG)	DW21B	DW20B, DW23B	172 A8	616	1935	892	5787	TL
E11*106R00/20*1 0489*00	VF 800/55R46 CFO (SB, SG)	DW28B	-	190 D / 190 A8	794	2067	955	6182	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.