

VIR 2500 - Data Sheet

Agriculture | Radial | IMP | TL | 7 Years

Salient Features & Benefits

VIR 2500, Specially designed VF radial tyre for modern seeding and trailer applications.

High Load Capacity at Low Pressure

- Advanced VF technology with reinforced carcass
- Carries standard load at 40% lower pressure, reducing stress on soil and tyre

Enhanced Traction

- Block tread with centre zig-zag rib
- Ensures lateral grip and smooth manoeuvrability in tilled fields and wet terrain

Longer Tyre Life & Field Protection

- Special Stubble Resistant (SSR) compound
- Guards against cuts, cracks, and stubble, extending tyre life on harsh fields

Low Soil Compaction

- Wider footprint.
- Minimises soil damage and enhances crop yield potential

Puncture Resistance & Durability

- Extra strong casing with high-performance steel belts
- Provides even load distribution and protects against sharp residues and debris



Machineries



Implement

Standard: ProductComponent.International Standards

Technical Specifications

ECE	Size	Recommended Rim	Alternate Rim	PR & LI/SI	Unloaded Dimension (mm)		Static Load Radius (mm)	Rolling Circumference (mm)	Type
					SW	OD			
-	VF 240/80R15 (SB SG)	8LB	-	126 D	245	765	349	2288	TL
E11*106R00/20*10 483*00	VF 265/85R15 (SB SG)	8LB	-	129 D	261	832	377	2488	TL
E11*106R00/20*10 482*00	VF 340/60R15 (SB SG)	10LB	-	129 D	333	789	359	2360	TL
E11*106R00/21*11 211*00	VF 280/70R15 (SB SG)	8LB	-	140 D	280	773	352	2321	TL
E11*106R00/21*11 212*00	VF 320/70R15 (SB SG)	10LB	-	145 D	320	829	375	2489	TL
-	VF 380/70R15 (SB SG)	12	-	152 D	380	913	352	2742	TL
E11*106R00/21*11 213*00	VF 380/55R16.5 (SB SG)	12	-	148 D	380	837	382	2513	TL
E11*106R00/20*86 72*00	VF 380/60R16.5 (SB SG)	12	-	147 D	380	875	398	2628	TL
E11*106R00/20*10 487*00	VF 480/45R17 (SB SG)	16	-	155 D	489	864	394	2584	TL
E11*106R00/20*10 486*00	VF 500/50R17 (SB SG)	16	-	156 D	503	932	422	2787	TL
E11*106R00/21*11 095*00	VF 360/65R17.5 (SB SG)	10.5x17.5	-	148 D	359	913	416	2731	TL

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.